



Slotted Power Bits

	OVERALL LENGTH	SCREW SIZE	BLADE THICKNESS	BODY DIAMETER	PART NO.
1/4" HEX DRIVE SHANK					
	1-15/16"	1F-2R	.026	.122	20-1S
		2F-3R	.028	.134	20-2S
		3F-4R	.032	.154	20-3S
		4F-5R	.034	.187	20-4S
		5F-6R	.036	.215	20-5S
		5F-6R	.036	.250	20-6S
		6F-7R	.038	.250	20-7S
		8F-10R	.042	.281	20-8S
		10F-12R	.046	.312	20-9S
		12F-14R	.050	.350	20-10S
	3"	1F-2R	.026	.122	23-1S
		2F-3R	.028	.134	23-2S
		3F-4R	.032	.154	23-3S
		4F-5R	.034	.187	23-4S
		5F-6R	.036	.215	23-5S
		6F-7R	.038	.250	23-6S
		8F-10R	.042	.281	23-8S
		10F-12R	.046	.312	23-9S
		12F-14R	.050	.350	23-10S
		14F-16R	.055	.350	23-12S
	3-1/2"	1F-2R	.026	.122	27-1S
		2F-3R	.028	.134	27-2S
		3F-4R	.032	.154	27-3S
		4F-5R	.034	.187	27-4S
		5F-6R	.036	.215	27-5S
		5F-6R	.036	.250	27-6S
		6F-7R	.038	.250	27-7S
		8F-10R	.042	.281	27-8S
		10F-12R	.046	.312	27-9S
		12F-14R	.050	.350	27-10S
		14F-16R	.055	.350	27-12S
	6"	1F-2R	.026	.122	28-1S
		2F-3R	.028	.134	28-2S
		3F-4R	.032	.154	28-3S
		4F-5R	.034	.187	28-4S
		5F-6R	.036	.215	28-5S
		5F-6R	.036	.250	28-6S
		6F-8R	.040	.250	28-7S
		8F-10R	.042	.281	28-8S
		10F-12R	.046	.312	28-9S
		12F-14R	.050	.350	28-10S
		14F-16R	.055	.350	28-12S