
FENDER Steel



|              | Fender Washers              |                     |       |           |      |  |             |                   |                     |       |           |      |  |
|--------------|-----------------------------|---------------------|-------|-----------|------|--|-------------|-------------------|---------------------|-------|-----------|------|--|
| Size         | Inside<br>Diam.<br>(± .010) | Outside<br>Diameter |       | Thickness |      | Approx.<br>number<br>of STEEL<br>washers per<br>carton | C:          | Inside            | Outside<br>Diameter |       | Thickness |      | Approx.<br>number<br>of STEEL<br>washers per<br>carton |
|              |                             | Max                 | Min   | Max       | Min  | 25 Lbs.<br>(Zinc, Black<br>Oxide or<br>Plain finish)   | Size        | Diam.<br>(± .010) | Max                 | Min   | Max       | Min  | 25 Lbs.<br>(Zinc, Black<br>Oxide or<br>Plain finish)   |
| 10 x 11/16   | .219                        | .698                | 0.678 | .080      | .036 | 4675   | 3/8 x 1     | .406              | 1.010               | 0.990 | .132      | .036 | 2050   |
| 10 x 3/4     | .223                        | .779                | 0.742 | .080      | .036 | 3500   | 3/8 x 1-1/4 | .410              | 1.279               | 1.242 | .132      | .036 | 690 - 1175   |
| 10 x 7/8     | .219                        | .885                | 0.865 | .080      | .036 | 2500   | 3/8 x 1-1/2 | .410              | 1.529               | 1.492 | .132      | .036 | 490 - 825  |
| 10 x 1       | .223                        | 1.018               | 0.992 | .084      | .036 | 1750   | 3/8 x 1-3/4 | .410 or<br>.422   | 1.779               | 1.742 | .132      | .047 | 565 - 1130   |
| 10 x 1-1/4   | .223                        | 1.279               | 1.242 | .084      | .036 | 1572   | 3/8 x 2     | .410 or<br>.422   | 2.029               | 1.992 | .080      | .047 | 487  |
| 10 x 1-1/2   | .223                        | 1.529               | 1.492 | .080      | .036 | 880  | 3/8 x 2-1/2 | .422              | 2.510               | 2.490 | .080      | .051 | 256  |
| 10 x 2       | .219                        | 2.010               | 1.990 | .080      | .036 | 398  | 1/2 x 1-1/4 | .535              | 1.279               | 1.242 | .080      | .051 | 1337   |
| 1/4 x 1      | .285                        | 1.029               | 0.992 | .132      | .036 | 1075 - 1875  | 1/2 x 1-1/2 | .535              | 1.529               | 1.492 | .080      | .051 | 1000   |
| 1/4 x 1-1/4  | .285                        | 1.279               | 1.242 | .132      | .036 | 635 - 1150   | 1/2 x 1-3/4 | .535              | 1.779               | 1.742 | .080      | .051 | 537  |
| 1/4 x 1-1/2  | .285                        | 1.529               | 1.492 | .132      | .036 | 775  | 1/2 x 2     | .535              | 2.029               | 1.992 | .132      | .051 | 234 - 425  |
| 1/4 x 1-3/4  | .285                        | 1.779               | 1.742 | .080      | .036 | 550  | 1/2 x 2-1/2 | .535              | 2.529               | 2.492 | .080      | .051 | 334  |
| 1/4 x 2      | .285                        | 2.029               | 1.992 | .080      | .036 | 405  | 1/2 x 3     | .531              | 3.010               | 2.990 | .080      | .051 | 177  |
| 5/16 x 1-1/4 | .348                        | 1.279               | 1.242 | .132      | .036 | 665 - 1200   | 5/8 x 1-1/4 | .688              | 1.260               | 1.240 | .084      | .074 | 1795   |
| 5/16 x 1-1/2 | .348                        | 1.529               | 1.492 | .132      | .036 | 440 - 800  | 5/8 x 1-1/2 | .688              | 1.529               | 1.492 | .084      | .074 | -  |
| 5/16 x 1-3/4 | .348                        | 1.779               | 1.742 | .080      | .051 | 664  | 5/8 x 2     | .688              | 2.010               | 1.990 | .080      | .051 | 507  |
| 5/16 x 2     | .348                        | 2.029               | 1.092 | .080      | .036 | 410  | 5/8 x 3     | .688              | 3.010               | 2.990 | .080      | .051 | 182  |
| 5/16 x 2-1/2 | .344                        | 2.510               | 2.490 | .080      | .036 | 250  | 3/4 x 2     | .812              | 2.015               | 1.985 | .080      | .051 | 577  |
|              |                             |                     |       |           |      |  | 7/8 x 2-1/2 | .938              | 2.515               | 2.485 | .118      | .101 | 357  |

| Description                 | A flat washer with significantly more surface area than a USS or SAE washer. They are also made from a thinner gauge metal than most flat washers.   |  |  |  |  |  |  |  |
|-----------------------------|--|--|--|--|--|--|--|--|
| Applications/<br>Advantages | Used where an extra wide bearing surface is required. Originally designed for auto body repair work, they are also used in sheet metal, plumbing, and electrical work. Also used to attach signs to posts, to install drywall and wood paneling. |  |  |  |  |  |  |  |
|                             | Steel  |  |  |  |  |  |  |  |
| Material                    | Washers shall be punched from hot-rolled, hot-rolled and pickled or cold-rolled steel, or shall be machined from bar stock or tubing, or may be forged at the manufacturer's option.   |  |  |  |  |  |  |  |
| Plating                     | Fender washers are usually provided zinc plated or with no finish.   |  |  |  |  |  |  |  |